YI WASTE CONE

El-mesaha, 9 St., Maadi, Cairo, Egypt. | +2 01282036093 | info@shcegypt.com | WWW.SHCEGYPT.COM

FIRE PUMPS WATE CONE

YI WASTE CONE is fabricated in accordance with NFPA 20 requirements, designed to provide quick and easy visual verification of flow in fire protection system, typically installed downstream the diesel engine main pressure relief valve, equipped with Two sight glasses extending from the center allow operators to observe the flow and ensure that fire pump pressure relief valve is working correctly.



Product Features

- Designed to use with UL/FM approved fire pump pressure relief valves.
- Equipped with 2x2" bronze Sight glasses assembly.
- FF/RF Flanges, ANSI Class 150, Other available on request.
- Electrostatic coating finish, Other available on request.

MODEL	Rated Pump Flow Rate	SIZE INLET X OUTLE	Standard Flanges
SHC - YI - 01	250 GPM	2"X2½"	RF/FF Class 150
SHC - YI - 02	250 GPM	3"X4"	RF/FF Class 150
SHC - YI - 03	500 GPM	3"X6"	RF/FF Class 150
SHC - YI - 04	750 GPM	4"X6"	RF/FF Class 150
SHC - YI - 05	1000 GPM	4"X8"	RF/FF Class 150
SHC - YI - 06	1250 - 1500 GPM	6"X8"	RF/FF Class 150
SHC - YI - 07	2000 - 2500 GPM	6"X10"	RF/FF Class 150
SHC - YI - GN	-	AS Per Request	

© Copyright STEADY HAND CONSTRUCTION LLC. All Rights Reserved.
The information contained in this document is subject to change without notice.
SHC shall not be liable for any errors contained herein.